



# TAMDAR

Tropospheric Airborne Meteorological Data Reporting

## System Implementation

---

NASA WxAP Review

June 2, 2004

---

# Topics

---



- Program Background
  - NASA-AirDat Partnership
  - TAMDAR Sensor and System
  - Implementation of TAMDAR System
    - Deployment Plans
    - Datalink
    - AirDat Infrastructure
    - AirDat/TAMDAR Products and Services
-

# TAMDAR Background

---



NASA-backed aviation safety initiative

- Real time reporting of hazardous conditions including icing & turbulence
- Improved aviation weather information
- Produce automatic, non-subjective, electronic pilot reports

Multi-function airborne atmospheric sensor

- Self-contained
  - Minimize aircraft interfaces
  - Minimize certification issues, time & cost
-

# The TAMDAR sensor

---



Detects and determines:

- Ice presence
  - Median and peak turbulence
  - Static pressure and pressure altitude
  - Air temperature (Mach corrected)
  - Relative humidity
  - Indicated and true airspeed
  - Winds aloft
  - Built-in GPS
-

# NASA-AirDat partnership

---



- Relationship has been very productive
  - NASA has actively supported AirDat's development of the TAMDAR sensor over the past four years
  - This partnership has facilitated successful technology development and beta testing on numerous aircraft
  - NASA and AirDat are currently implementing the first regional deployment of a fully-certified TAMDAR system
-

# NASA-AirDat partnership

---



## NASA

- Provided design guidance and input
  - Arranged flight test bed aircraft
  - Developed relationships with NOAA/FSL/NWS and FAA
  - Identified and contacted potential carriers
  - Provided substantial R&D support
-

# NASA-AirDat partnership

---



## AirDat

- Designed and developed sensor
  - Conducted test flights
  - Certified and is manufacturing sensor
  - Implemented TAMDAR data center and infrastructure
  - Planning TAMDAR system implementation nationwide
  - Invested substantial private capital in the TAMDAR project
-

# TAMDAR probe on Saab 340

---





# TAMDAR probe on Saab 340

---

**AIR**DAT




# TAMDAR probe on Boeing 727


---



# TAMDAR airborne unit



# The TAMDAR System



# Observations and reports

---



- Pressure-based observations with time defaults (preferred by meteorologists)
  - Automatically controlled and buffered by TAMDAR sensor—no CMS required
  - Active control from AirDat data center
    - Adjustable by remote command
      - Intervals and defaults
      - Calibration constants
      - Concentration and distribution of observations
  - Upgrades to firmware can be easily bootloaded
-

# Deployment plan

---



## CONUS deployment

- Mesaba Saab 340 fleet in Great Lakes Region (64 aircraft—beginning June 2004)
  - ~ 1500 aircraft—next two years
-

# Carrier participation benefits

---




## Enhanced flight safety and operations

### Weather information

- Real time icing and turbulence reports
- Improved operational forecasts
- Real time weather information to the cockpit


# Aviation weather products



Display  
Derived  
from FSL  
ACARS  
display  
developed  
by Bill  
Moninger




# Aviation weather products



Various display types are possible


This is an example of a ground-based meteorological tool

# Aviation weather products



# Aviation weather products

24 hr forecast valid Wed, 31 Mar 2004, 6 am CST (12Z)  
Weather



# Carrier participation benefits


---



## Enhanced operational information





- OOOI times, departure and arrival airports
  - GPS tracking
  - Text messaging
  - Airborne trouble ticketing
  - Other systems monitoring
-

# Real-time aircraft tracking



The TAMDAR system enables real-time global tracking of all equipped aircraft

# Real-time aircraft tracking



# Datalink criteria

---





- Available now
  - Financial stability / reliability
  - Two-way capability
    - Observation downlinks
    - Control uplinks
  - Minimal latency
  - Global coverage at all altitudes to ground
  - Affordability
  - Additional capabilities
-

# Aircraft datalink capabilities

---


- Iridium Satellite selected (AirDat is a VAR)
- 66 four-way cross-linked LEO satellites provide complete global coverage and minimal latency
- Satellites relay messages and need not be in same footprint as the gateway





# Aircraft datalink capabilities

---



The AirDat/Iridium network provides an autonomous global communication channel to/from each aircraft.

TAMDAR does not interfere or compete with existing flight-critical communication systems.

# AirDat Facilities

---



To support TAMDAR, AirDat has established:

- A business office and data center in Raleigh-Durham, NC
  - An office/R&D facility in Evergreen, CO
-

# Facilities

---



## Operations Center (NC)

- Business office
- Network operations mgmt.
- Data receiving, archiving, processing and distribution
- TAMDAR lifecycle mgmt.
- Data center in same building
- Located in technology park 5 min. from RDU airport



# Facilities

---




## Research / Development (CO)

- Engineering & testing
- Certification management
- Manufacturing management
- Observation data QA
- Fully equipped electronics lab
- Wind tunnel
- 20 mi. from Denver & Boulder



# Facilities



## AirDat Network Architecture

# Ongoing partnership with NASA

---



- Many areas for cooperation in the future
  - Continued opportunities to develop TAMDAR products
    - Achieve NASA AWIN & WINCOMM safety goals
    - Development of TAMDAR based aviation hazardous condition displays
    - Integration of TAMDAR data into forecasts for enhanced aviation weather
    - Integration of TAMDAR data into cockpit displays
  - Utilization of TAMDAR/AirDat infrastructure to improve aviation safety and services
-

# Aviation weather products

**0 hr forecast valid Tue, 30 Mar 2004, 6 am CST (12Z)**  
**Aircraft Icing**

